

KSWM Series



| Model | | | KSWM009-H113 | KSWM012-H113 | KSWM018-H213 | KSWM024-H213 |
|---------------------------------|------------------------------|---------|----------------|----------------|--------------------|--------------------|
| Power supply | | Ph-V-Hz | 1, 115V~, 60Hz | 1, 115V~, 60Hz | 1, 208/230V~, 60Hz | 1, 208/230V~, 60Hz |
| Cooling | Capacity | Btu/h | 9500 | 12000 | 18000 | 24000 |
| | Input | W | 800 | 1090 | 1530 | 2000 |
| | Rated current | A | 7,5 | 10 | 6,7 | 8,8 |
| | SEER | Btu/w.h | 13,28 | 13 | 13,33 | 13,58 |
| Heating | Capacity | Btu/h | 10000 | 13000 | 18000 | 24000 |
| | Input | W | 900 | 1160 | 1630 | 2000 |
| | Rated current | A | 7,3 | 10,6 | 7,1 | 8,8 |
| | HSPF | Btu/w.h | 8,03 | 8,64 | 8,05 | 8,66 |
| Moisture Removal | | L/h | 0,9 | 1,35 | 1,55 | 2 |
| Max. input consumption | | W | 1050 | 1460 | 2100 | 2950 |
| Max. current | | A | 10,2 | 14 | 10,2 | 14 |
| Starting current | | A | 40 | 47 | 32,6 | 34.8 A |
| Indoor air flow (Hi/Mi/Lo) | | cfm | 400/320/250 | 440/370/330 | 620/540/490 | 780/680/600 |
| Indoor noise level (Hi/Mi/Lo) | | dB(A) | 41/35/28 | 45/41/38 | 45/43/41 | 50/47/44 |
| Outdoor noise level | | dB(A) | 53 | 55 | 58 | 59 |
| Refrigerant type/ Charge amount | | oz | R410A/ 38 | R410A/ 48 | R410A/ 72 | R410A/ 86 |
| Design pressure | | psi | 650 | 650 | 650 | 650 |
| Operation temp | | F | 62 to 86 | 62 to 86 | 62 to 86 | 62 to 86 |
| Ambient temp | | F | 19 to 115 | 19 to 115 | 19 to 115 | 19 to 115 |
| Application area | | Sq Ft | up to 400 | 400 - 600 | 600-800 | 800-1200 |
| Compressor | Type | | ROTARY | ROTARY | ROTARY | Rotary |
| | Brand | | GD TOSHIBA | GD TOSHIBA | GD TOSHIBA | GD TOSHIBA |
| Refrigerant piping | Liquid side/ Gas side | in OD | 1/4" / 3/8" | 1/4" / 1/2" | 1/4" / 1/2" | 3/8" / 5/8" |
| | Max. refrigerant pipe length | ft | 32 | 32 | 50 | 65 |
| | Max. difference in level | ft | 16 | 16 | 26 | 32 |
| Indoor unit | Dimension (W×H×D) | in | 32×11×7.7 | 35.6×11.3×9.3 | 49.2×12.8×9 | 49.2×12.8×9 |
| | Packing (W×H×D) | in | 36×14.2×10.8 | 40.1×15×12.9 | 53×17×13.2 | 53×17×13.2 |
| | Net/Gross weight | LBS | 17.6 / 24 | 25.3/33 | 40/55 | 40/55 |
| Outdoor unit | Dimension(W×D×H) | in | 30.7×9.9×21.2 | 30×11.2×23.2 | 33.3×13.2×27.4 | 35.2×13×33.9 |
| | Packing (W×D×H) | in | 35.8×13.2×22.6 | 34.9×14×25.8 | 38×15.6×29.7 | 41×15.6×36 |
| | Net/Gross weight | LBS | 73/79 | 84/90 | 120/128 | 151/161 |

NOTE: SPECIFICATIONS AND PERFORMANCE DATA LISTED HEREIN ARE SUBJECT TO CHANGE WITHOUT NOTICE